

JP61-187531U

---

Job No.: 1505-127124

Translated from Japanese by the McElroy Translation Company

800-531-9977

[customerservice@mcelroytranslation.com](mailto:customerservice@mcelroytranslation.com)

(19) JAPANESE PATENT OFFICE (JP)

(11) PATENT APPLICATION  
PUBLICATION

(12) KOKAI TOKUHYO PATENT GAZETTE (U)

Sho 61[1986]-187531

(51) Int. Cl.<sup>4</sup>: Identification Codes: Sequence Nos. for Office Use (43) Publication Date November 22, 1986  
A 46 B 7/06 8206-3B

Examination Request: Not filed

No. of Claims: (Total of 4 pages)

---

(54) Title TOOTHBRUSH WITH A MOVABLE TRANSPLANTED BRISTLE PART

(21) Filing No.: Sho 60[1985]-70765

(22) Filing Date: May 15, 1985

(72) Inventor: Shigeo Koshichi  
1-40-8 Sasatsuka, Shibuya-ku, Tokyo-to

(71) Applicant: Shigeo Koshichi 1-40-8 Sasatsuka, Shibuya-ku, Tokyo-to

### Claim

A toothbrush with a movable transplanted bristle part characterized by consisting of a brush part that has a supporting rod vertically provided at the opposite side of the transplanted bristle part and a handle part that has clearance area in the head part, and the supporting rod of the aforementioned brush part is freely inserted in a manner so that it can freely move inside the clearance area in the aforementioned head part of the handle part.

### Brief description of the figures

Figure 1 is a diagonal view diagram that shows the disassembled structure of Application Example 1 in this invention. Figure 2 is a side view diagram of a vertical cross-section at II-II of the parts in Figure 1 that are assembled together. Figure 3 is a front view diagram of a vertical cross-section at III-III of the parts in Figure 1 that are assembled together. Figures 4, 5, and 6 are diagonal view diagrams that show other clearance areas in Application Example 1 in this invention. Figure 6 is a diagonal view diagram that shows another clearance area in Application Example 1 in this invention. Figure 7 is a diagonal view diagram that shows Application Example 2 in this invention. Figure 8 is a side view diagram of a vertical cross-section at VIII-VIII of Figure 7. Figure 9 is a front view diagram of a vertical cross-section at IX-IXI of Figure 7. Figure 10 is a diagonal view diagram that shows another engagement piece in Application Example 2 in this invention. Figure 11 is a diagonal view diagram that shows the upper face of another clearance area in Application Example 2 in this invention. Figure 12 is a side vertical



Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11






Figure 12




Figure 13




Figure 14




Figure 15




Figure 16

Amendment on March 12, 1986

The range of the claim for Japanese Utility Model registration will be amended as below.

#### Claim

A toothbrush with a movable transplanted bristle part characterized by consisting of a brush part that has a supporting part provided at the opposite side of the transplanted bristle part and a handle part that has clearance area in the head part, and the supporting part of the aforementioned brush part is arranged in a manner so that it can freely move inside the clearance area in the aforementioned head part of the handle part.